

EA19 Separated Downlight

PRODUCT FEATURES

- Open area and corridor lens optional
- Manual test and self-test selectable by dip switch
- LiFePO₄ battery easy to replace



ORDERING INFORMATION

SAMPLE NUMBER: EA19-01S-0103-O-W

Series	Generation	Category	EM Power	Duration	Lens	Color	Catalog
EA19 =EU&Australia emergency light # 19 series	01 =Gen1	Manual test S =Self test	1.2W	3h	O =Open area C =Corridor	W =White B =Black	EA19-01-0103-O-W EA19-01-0103-C-W EA19-01-0103-O-B EA19-01-0103-C-B EA19-01S-0103-O-W EA19-01S-0103-C-W EA19-01S-0103-O-B EA19-01S-0103-C-B

GENERAL INFORMATION

Light Source LED	Colour/Finish White/Black
Certificate CE UKCA	Warranty (include battery) 5 years
IP grade IP20	Installation Recessed mounted Ceiling mounted

TECHNICAL INFORMATION

Input 220-240V	Beam Angle 155/110	CRI 80
CCT 6500K	SDCM 6	Lumen 215
Operating Temp 0-45°C	Emergency Output Duration >180 minutes	

DIMENSION(mm) Lamp:Ø95*35.9 Driver:190*28*26

PHOTOMETRY

